



↓ PRODUCT DESCRIPTION

The Line 030 has outputs of 15 watts per meter. It fits discreetly into display windows, shelves, and niches, and give a diffuse light. With an initial length of 22 cm, this LED linear can be combined to create the required length. It offers a range of colour temperatures for harmonious lighting. Its compact clipped profile enables it to be oriented at an angle of 40 or 180 degrees, and it is very easy to install and fix.

↓ OUTPUT

15W /m

↓ LUMENS

1200 lm/m

↓ CRI

IRC80

IRC90

↓ POWER SUPPLY

24V

↓ DIMMING



DMX

↓ DEGREES

↓ IP RATING

IP 40

↓ USE



↓ COLOUR TEMPERATURE

2700K

3000K

3500K

4000K

5000K

↓ STANDARDS COMPLIANCE

EN 62471

EN 60598-1

EN 60598-2



↓ COLOURS

AL

BK

↓ SOURCES

- Luminous flux according to Bining : 1200 lumens by meter;
- Colour temperature : from 2700 K to 5000 K;
- Service Range : 70 % of nominal flux after 50000 hours;
- Colour Rendering Index : CRI 80 or CRI 90.

↓ OPTICAL CHARACTERISTICS

- Lenticular filter for profile. Transmission > 90%;
- Beam Angle : 115°.

↓ ELECTRICAL CHARACTERISTICS

- Power Supply Line 030 : Constant voltage 24V;
- Supply Connectors : Wire outlet section 0,5mm²/ AWG20, 200 cm, polarised, pre-stripped;
- Power Output : 15 W per meter;
- Electrical Classification : Class III SELV device.

↓ MECHANICAL CHARACTERISTICS

- Operating temperature : - 5° + 40°;
- Lengths by multiples of 20 cm + 2cm;
- Delivered with Aluminum profile (including end caps -2 x 2 mm thick, filter & mounting clips);
- Adjustable profile with a total angle of 40° or 180° (depending on the mounting clip);
- ROHS components;
- Inside use only.

↓ SPECIFICITIES

- 3 years guarantee.

↓ CLASSIFICATION

Product Ref.	LI030	
Specification	AA	
Colour	Aluminium	AL
	Black	BK
Colour temperature	2700K	27
	3000K	30
	3500K	35
	4000K	40
	5000K	50
Lengths	22 cm	020
	42 cm	040
	62 cm	060
	82 cm	080
	102 cm	100
	122 cm	120
	142 cm	140
	162 cm	160
	182 cm	180
	202 cm	200
REFERENCE	LI030 - AA - AL - 30 - 180	

↓ LENGTHS | POWER

Lengths* (cm)	Power (w)
22	3
42	6
62	9
82	12
102	15
122	18
142	21
162	24
182	27
202	30

* Overall length including aluminum profile, cover, protective endpiece, and spare cable outlet