



↓ PRODUCT DESCRIPTION

Part of the «C» range, with its 360-degree magnetic ball joint and mini cap, this unique small spot is emblematic of Loupi's know-how. Used for accent lighting, it exploits the advantages of LED technology to the full: less bulk, lower energy consumption and greater efficiency. a small unit that lights like a big one.

↓ OUTPUT

3W

↓ LUMENS

200lm

↓ CRI

IRC90

↓ POWER SUPPLY

700mA

↓ DIMMING

1-10V DMX CASAMBI

↓ DEGREES

10° 18° 28° 40° ELL

↓ IP RATING

IP 40

↓ USE

↓ COLOUR TEMPERATURE

2400K 2700K 3000K 3500K 4000K 5000K

↓ STANDARDS COMPLIANCE

EN 62471 EN 60598-1 EN 60598-2 CE

↓ COLOURS

BK WH CUSTOM

↓ SOURCES

- Luminous flux according to Bining: 200 lumens;
- Colour temperature: 2400 K to 5000 K;
- Service Range: 70 % of nominal flux after 50 000 hours;
- Colour Rendering Index: CRI 90.

↓ OPTICAL CHARACTERISTICS

- PMMA acrylic lens, efficiency ~90 %;
- Available degrees: 10°, 18°, 28°, 40° & Elliptic.

↓ ELECTRICAL CHARACTERISTICS

- Constant current supply: 700mA;
- Supply connection: Corrected proprietary connector system, polarised output connectors;
- Power consumption to 3W max, excluding supply;
- Electrical Classification: Class III SELV device.

↓ MECHANICAL CHARACTERISTICS

- Articulating base, patented magnetic ball joint;
- Mounting on hook;
- Operating temperature: -5° +40°;
- ROHS components;
- Interior use only.

↓ SPECIFICITIES

- Electrolytic treatment available;
- 3 years guarantee.

↓ CLASSIFICATION

Product Ref.	SC001		
Specification	A		
Colour	Black		BK
	White		WH
	Chromium		CU
	Gold		CU
	Brushed Nickel		CU
	RAL		CU
Colour temperature	2400K		24
	2700K		27
	3000K		30
	3500K		35
	4000K		40
	5000K		50
Degrees	10°		10
	18°		18
	28°		28
	40°		40
	Elliptic		EL
REFERENCE	SC001 - A - BK - 24 - 10		

Spot C

ACCESSORIES

REF: SC001-A

SPOTS EN

↓ CONNECTORS POWER SUPPLY IN 24V / OPTICAL ACCESSORIES



ACSC001OPNIDABBKD28
Honeyc SPOT C
Ø28mm



ACSC001OPSNOOTBKL14
Snoot SPOT C
Ø28mm Lg 14mm Noir



ACSC001OPSNOOTBKL20
Snoot SPOT C
Ø28mm Lg 20mm Noir



ACSC001COCIRCPXX700
Piccolo circuit with sheath
heat-shrinkable for SPOT C

↓ CONNECTORS INDEPENDENT CONNECTION TO BATTERIES



ACSCXXXCOPLITHXX010
Pack Lithium 10,4Ah



ACSCXXXCOCLITHXX35
Chargeomr Pack Lithium
Charger 29,4V 3,5A



ACSCXXXCOPLITHXX26
Pack Lithium 2,6Ah



ACSCXXXCOCLITHXX06
Charger Pack Lithium
Charger 29,4V 0,6A



EUROPLUG

↓ FIXATION/FINITION



ACSCXXXFIPATERBK*APP
Surface mounted SPOT
Black (BK), White (WH), Custom (CU)



ACSCXXXFIPATERBKENC
Recessed peg SPOT
Black (BK), White (WH), Custom (CU)



ACSC0XXFIPATLGWHC
Tall peg SPOT
Black (BK), White (WH), Custom (CU)

↓ SERIAL WIRING



ACSC001COJONCTBK*100
Junction cable Black (BK),
White (WH) 100 cm



ACSC001CONEGATBK*080
Negative cable Black (BK),
White (WH) 80 cm



ACSC001COPOSITBK*080
Positive cable Black (BK),
White (WH) 80 cm