



↓ PRODUCT DESCRIPTION

This high-efficiency articulated microspot, part of the «D» range offers a high degree of lighting efficiency despite its small size. Used for precision luminous flux, its sleek, miniaturized design makes it very easy to fit in shop windows, display units, and other small spaces.

↓ OUTPUT

1,5W

↓ LUMENS

150lm

↓ CRI

IRC90

↓ POWER SUPPLY

500mA

↓ DIMMING

1-10V DMX CASAMBI

↓ DEGREES

16° 24° 40° ELL

↓ IP RATING

IP 40

↓ USE

↓ COLOUR TEMPERATURE

2400K 2700K 3000K 3500K 4000K 5000K

↓ STANDARDS COMPLIANCE

EN 62471 EN 60598-1 EN 60598-2

↓ COLOURS

BK WH CUSTOM

↓ SOURCES

- Luminous flux according to Bining: 150 lumens;
- Colour temperature: 2400 K to 5000 K;
- Service Range: 70 % of nominal flux after 25 000 hours;
- Colour Rendering Index: CRI 90.

↓ OPTICAL CHARACTERISTICS

- PMMA acrylic lens, efficiency ~90 %;
- Available degrees: 16°, 24°, 40° & Elliptic.

↓ ELECTRICAL CHARACTERISTICS

- Constant current supply: 500 mA;
- Supply connection: Polarised output connectors;
- Power consumption to 1.5W max, excluding supply;
- Electrical Classification: Class III SELV device.

↓ MECHANICAL CHARACTERISTICS

- Articulating base;
- Mounting on hook;
- Operating temperature: -5° +40°;
- ROHS components;
- Interior use only.

↓ SPECIFICITIES

- Electrolytic treatment available;
- 3 years guarantee.

↓ CLASSIFICATION

Product Ref.	SD000			
Specification	A			
Colour	Black			BK
	White			WH
	Aluminum			AL
	Chromium			CU
	Brass			CU
	RAL			CU
Colour temperature	2400K			24
	2700K			27
	3000K			30
	3500K			35
	4000K			40
	5000K			50
Degrees	16°			16
	24°			24
	40°			40
	Elliptic			EL
REFERENCE	SD000 - A - BK - 24 - 16			

Micro D

ACCESSORIES

REF : SD000-A

SPOTS EN

↓ CONNECTORS POWER SUPPLY IN 24V



ACSC000COCIRCPXX500
Piccolo circuit with sheath
heat-shrinkable for MICRO D

↓ CONNECTORS INDEPENDENT CONNECTION TO BATTERIES



ACSCXXXCOPLITHXX010
Pack Lithium 10,4Ah



ACSCXXXCOCLITHXX35
Charger Pack Lithium
Charger 29,4V 3,5A



ACSCXXXCOPLITHXX26
Pack Lithium 2,6Ah



ACSCXXXCOCLITHXX06
Charger Pack Lithium
Charger 29,4V 0,6A



EUROPLUG

↓ OPTICAL ACCESSORIES



ACMMC01OPNIDABBKD14C
Honeycomb MICRO D



ACSC000OPSNOOTBKL14C
Snoot Micro D

↓ FIXATION/FINITION



ACSCXXXFIPATERBKAPPC
Surface mounted SPOT
Black (BK), White (WH), Custom (CU)



ACSCXXXFIPATERBKENCC
Recessed peg SPOT
Black (BK), White (WH), Custom (CU)



ACSC0XXFIPATLGBKC
Tall peg SPOT
Black (BK), White (WH), Custom (CU)