



↓ PRODUCT DESCRIPTION

This minispot, with its articulation specific to the «D» range, is particularly popular among commercial architects and stage designers for its high efficiency and small size. Its discreet, elegant design offers a wide range of optical characteristics, colour temperatures, and finishes, and thus many possible configurations.

↓ OUTPUT

2,1W

↓ LUMENS

200lm

↓ CRI

IRC90

↓ POWER SUPPLY

700mA

↓ DIMMING

1-10V

DMX CASAMBI

↓ DEGREES

10° 29° 48° ELL

↓ IP RATING

IP 40

↓ USE

↑

↓ COLOUR TEMPERATURE

2400K 2700K 3000K 3500K 4000K 5000K

↓ STANDARDS COMPLIANCE

EN 62471 EN 60598-1 EN 60598-2 CE III

↓ COLOURS

BK WH CUSTOM

↓ SOURCES

- Luminous flux according to Bining: 200 lumens;
- Colour temperature: 2400 K to 5000 K;
- Service Range: 70 % of nominal flux after 25 000 hours;
- Colour Rendering Index: CRI 90.

↓ OPTICAL CHARACTERISTICS

- PMMA acrylic lens, efficiency ~90 %;
- Available degrees: 10°, 29°, 48° & Elliptic.

↓ ELECTRICAL CHARACTERISTICS

- Constant current supply: 700mA;
- Supply connection: Polarised output connectors;
- Power consumption to 2.1W max, excluding supply;
- Electrical Classification: Class III SELV device.

↓ MECHANICAL CHARACTERISTICS

- Articulating base;
- Mounting on hook;
- Operating temperature: -5° +40°;
- ROHS components;
- Interior use only.

↓ SPECIFICITIES

- Electrolytic treatment available;
- 3 years guarantee.

↓ CLASSIFICATION

Product Ref.	SD002				
Specification		A			
Colour	Black			BK	
	White			WH	
	Aluminum			AL	
	Chromium			CU	
	Gold			CU	
	RAL			CU	
Colour temperature	2400K				24
	2700K				27
	3000K				30
	3500K				35
	4000K				40
	5000K				50
Degrees	10°				10
	29°				29
	48°				48
	Elliptic				EL
REFERENCE	SD002 - A - BK - 24 - 10				

↓ CONNECTORS POWER SUPPLY IN 24V



ACSC000COCIRCPXX500
Piccolo circuit with sheath
heat-shrinkable forr MINI D

↓ CONNECTORS INDEPENDENT CONNECTION TO BATTERIES



ACSCXXXCOPLITHXX010
Pack Lithium 10,4Ah



ACSCXXXCOCLITHXX35
Charger Pack Lithium
Charger 29,4V 3,5A



ACSCXXXCOPLITHXX26
Pack Lithium 2,6Ah



ACSCXXXCOCLITHXX06
Charger Pack Lithium
Charger 29,4V 0,6A



EUROPLUG

↓ OPTICS ACCESSORIES



ACSD2NIDABBK023C
Honeycomb MINI D



ACSC000OPSNOOTBKL14C
Snoot MINI D

↓ FIXATION/FINITION



ACSCXXXFIPATERBKAPPC
Surface mounted SPOT
Black (BK), White (WH), Custom (CU)



ACSCXXXFIPATERBKENCC
Recessed peg SPOT
Black (BK), White (WH), Custom (CU)



ACSD0XXFIPATLGBKC
Tall peg SPOT
Black (BK), White (WH), Custom (CU)