



↓ PRODUCT DESCRIPTION

The L5 spot is the long version of the C5. This discreetly elegant light is surprisingly powerful for its small size. It provides high-quality interior lighting and unparalleled efficiency and reliability. Part of the «C» range, with its 360-degree magnetic ball joint, the Spot L5 is suited to a variety of general and precision lighting uses.

↓ OUTPUT

8W

↓ LUMENS

800lm

↓ CRI

IRC90

↓ POWER SUPPLY

0,7A

↓ DIMMING

1-10V



DMX

CASAMBI

↓ DEGREES

15°

25°

40°

ELL

↓ IP RATING

IP 40

↓ USE



↓ COLOUR TEMPERATURE

2700K

3000K

3500K

4000K

↓ STANDARDS COMPLIANCE

EN 62471

EN 60598-1

EN 60598-2



↓ COLOURS

BK

WH

CUSTOM

↓ SOURCES

- Luminous flux according to Bining: 800 lumens;
- Colour temperature: 2 700 K to 4 000 K (2 at 3 Macadam step);
- Service Range: 70 % of nominal flux after 50 000 hours;
- Colour Rendering IndexCRI 90.

↓ OPTICAL CHARACTERISTICS

- PMMA acrylic lens, efficiency ~90 %;
- Available degrees: 15°, 25°, 40° et ELL.

↓ ELECTRICAL CHARACTERISTICS

- Constant current supply: 700 mA;
- Supply connection: Polarised output connectors;
- Power consumption to 8 W max, excluding supply;
- Electrical Classification: Class III SELV device.

↓ MECHANICAL CHARACTERISTICS

- Articulating base, patented magnetic ball joint;
- Mounting on hook;
- Operating temperature: -5° +40°;
- ROHS components;
- Interior use only.

↓ SPECIFICITIES

- Electrolytic treatment available;
- 3 years guarantee.

↓ CLASSIFICATION

Product Ref.	SL005			
Specification		A		
Colour	Black		BK	
	White		WH	
	Aluminium		AL	
	Chromium		CU	
	Gold		CU	
	RAL		CU	
Colour temperature	2700K			27
	3000K			30
	3500K			35
	4000K			40
Degrees	15°			15°
	25°			25°
	40°			40°
	ELL			ELL
REFERENCE	SL005 - A - BK - 30 - 25°			

Spot L5

ACCESSORIES

REF: SL005-A

SPOTS EN

↓ CONNECTORS POWER SUPPLY IN 24V



ACSC005COCIRCPXX200
Piccolo circuit with sheath
heat-shrinkable for SPOT L5



ACSC005PINDABBKD36
hONEYCOMB L5



ACSC005OPSNOOTBKL14C
Snoot L5 LG



ACSC001OPSNOOTBKL20C
Snoot L5 LG

↓ CONNECTORS INDEPENDENT CONNECTION TO BATTERIES



ACSCXXXCOPLITHXX010
Pack Lithium 10,4Ah



ACSCXXXCOCLITHXX35
Charger Pack Lithium
Charger 29,4V 3,5A



ACSCXXXCOPLITHXX26
Pack Lithium 2,6Ah



ACSCXXXCOCLITHXX06
Charger Pack Lithium
Charger 29,4V 0,6A



EUROPLUG

↓ FIXATION/FINITION



ACSCXXXFIPATERBK*APP
Surface mounted SPOT
Black (BK), White (WH), Custom (CU)



ACSCXXXFIPATERBKENC
Recessed peg SPOT
Black (BK), White (WH), Custom (CU)



ACSC005FITIGSUBK***
Tall peg SPOT
Black (BK), White (WH), Custom (CU)