



↓ PRODUCT DESCRIPTION

Spot D12 - Powerful LED accent and architectural round spotlight with adjustable aluminium body.  
Threaded safety lock. Passive heat dissipation for source temperature control preserving LED life.  
Interchangeable lenses (15°, 25°, 40°, 50° Elliptical) by simple magnetic contact.


↓ PUISSANCE




↓ LUMENS




↓ IRC



↓ ALIMENTATION




↓ GRADATION




↓ DEGRÉS



↓ INDICE DE PROTECTION



↓ USAGE / UTILISATION



↓ TEMPÉRATURES DE COULEUR



↓ NORMES ET SÉCURITÉ



↓ COLORIS



## ↓ SOURCES

- Luminous flux according to Bining: 1200 lumens
- Colour temperature: 2700 K to 4000 K (2 at 3 Macadam step)
- Service Range: 70 % of nominal flux after 50 000 hours
- Colour Rendering Index: CRI 90.

## ↓ OPTICAL CHARACTERISTICS

- PMMA acrylic lens, efficiency ~90 %
- Available degrees: 15°, 25°, 40°, 50° and ELL.

## ↓ ELECTRICAL CHARACTERISTICS

- Constant supply voltage 1A
- Electric transmission by magnetic contact
- Reversible polarity and hot plug
- Power consumption to 12W max, excluding supply
- Electrical classification: Class III SELV device

## ↓ MECHANICAL CHARACTERISTICS

- Articulating base, patented magnetic ball joint
- Attachment by magnetic contact
- Operating temperature: -5° +40°
- ROHS components
- Interior use only

## ↓ SPECIFICITIES

- Electrolytic treatment available
- 3 years garantie

## ↓ NOMENCLATURES

Product Ref.	SD008				
Specification	A				
Color	Black		BK		
	White		WH		
	Aluminium		AL		
	Chrome		CU		
	Gold		CU		
	RAL		CU		
Température	2700K			27	
	3000K			30	
	3500K			35	
	4000K			40	
Degré	15°				15
	25°				25
	40°				40
	50°				50
	ELL				ELL
RÉFÉRENCE	SD008-	A-	BK-	27-	15

# Spot D12

## ACCESSORIES

REF : SD012-A

SPOTS EN

### ↓ CONNECTORS POWER SUPPLY IN 24V



**ACSC005COCIRCPXX200**  
Piccolo circuit with sheath  
heat-shrinkable for SPOT D8

### ↓ CONNECTORS INDEPENDENT CONNECTION TO BATTERIES



**ACSCXXXCOPLITHXX010**  
Pack Lithium 10,4Ah



**ACSCXXXCOCLITHXX35**  
Charger Pack Lithium  
Charger 29,4V 3,5A



**ACSCXXXCOPLITHXX26**  
Pack Lithium 2,6Ah



**ACSCXXXCOCLITHXX06**  
Charger Pack Lithium  
Charger 29,4V 0,6A



EUROPLUG

### ↓ FIXATION/FINITION



**ACSCXXXFIPATERBK\*APP**  
Surface mounted SPOT  
Black (BK), White (WH), Custom (CU)



**ACSCXXXFIPATERBKENC**  
Recessed peg SPOT  
Black (BK), White (WH), Custom (CU)



**ACSD0XXFIPATLGBK**  
Tall peg SPOT  
Black (BK), White (WH), Custom (CU)



**ACCSD0812NIDABBKC**  
Honeycomb  
SPOT D8 ou D12