



↓ PRODUCT DESCRIPTION

Attached by simple magnetic contact to a track equipped with low voltage conductors, this minispot is extremely easy to install, position, move, and replace. This Piccolo minispot has a magnetic ball joint and provides high-efficiency precision lighting. It is particularly popular among commercial architects and stage designers for its high-precision, high-intensity luminous flux, elegant design, and small size. It offers fully flexible lighting and a wide choice of optical characteristics, colour temperatures, and finishes, and can therefore be installed in multiple configurations.

↓ OUTPUT

2.6W

↓ LUMENS

200lm

↓ CRI

IRC90

↓ POWER SUPPLY

24V

↓ DIMMING

↓ DEGREES

10° 29° 48° ELL

↓ IP RATING

IP 40

↓ USE

↓ COLOUR TEMPERATURE

2400K 2700K 3000K 3500K 4000K 5000K

↓ STANDARDS COMPLIANCE

EN 62471 EN 60598-1 EN 60598-2 CE III ETL

↓ COLOURS

BK WH CUSTOM

↓ SOURCES

- Luminous flux according to Bining: 200 lumens;
- Colour temperature: 2400 K to 5000 K;
- Service Range: 70 % of nominal flux after 25 000 hours;
- Colour Rendering Index: CRI 90.

↓ OPTICAL CHARACTERISTICS

- PMMA acrylic lens, efficiency ~90 %;
- Available degrees: 10°, 29°, 48° & Elliptic.

↓ ELECTRICAL CHARACTERISTICS

- Constant supply voltage 24V;
- Electric transmission by magnetic contact;
- Reversible polarity and hot plug;
- Power consumption to 2.6W max, excluding supply;
- Electrical Classification: Class III SELV device.

↓ MECHANICAL CHARACTERISTICS

- Electronic circuit encased in a fire proof polycarbonate housing;
- Articulating base, patented magnetic ball joint;
- Attachment by magnetic contact;
- Operating temperature: -5° +40°;
- ROHS components;
- Interior use only.

↓ SPECIFICITIES

- Mechanical adjustment of its intensity (from 5% to 100%) by a «calibrator»;
- Electrolytic treatment available;
- Color track profile: White or Black;
- 3 years guarantee.

↓ CLASSIFICATION

Product Ref.	SC002			
Specification		P		
Colour	Aluminium			AL
	Black			BK
	White			WH
	Chromium			CU
	Gold			CU
	RAL			CU
Colour temperature	2400K			24
	2700K			27
	3000K			30
	3500K			35
	4000K			40
	5000K			50
Degrees	10°			10
	29°			29
	48°			48
	Elliptic			EL
REFERENCE	SC002 - P - BK - 27 - 29			

Mini C Piccolo

ACCESSORIES

REF: SC002-P

TRACKS 

↓ OPTICAL ACCESSORIES



ACMMC01OPNIDABBKD12
Honeycomb MINI C
Ø 22.8mm



ACSC0000PSNOOTBKL14C
Snoot MINI C
Ø 22.8mm Lg 10mm Noir