

↓ PRODUCT DESCRIPTION

Part of the D range, with its specific articulation, this unique small spot is emblematic of Loupi expertise. Used for accent lighting, it exploits the advantages of LED technology to the full: less bulk, lower energy consumption and greater efficiency. a small unit that lights like a big one.

↓ OUTPUT (PEG)

3W

↓ OUTPUT (TRACK, RCA)

3.5W

↓ CRI

IRC90

↓ USE

↓ IP

IP 40

↓ POWER SUPPLY (PEG)

700mA

↓ LUMENS

300lm

↓ DEGREES

10° 18° 28° 40° ELL

↓ POWER SUPPLY (TRACK, RCA)

24V

↓ DIMMING

1-10V BALL CASAMBI DMX

↓ COLOUR TEMPERATURE

2400K 2700K 3000K 3500K 4000K 5000K

↓ STANDARDS COMPLIANCE

EN 62471 EN 60598-1 EN 60598-2 CE III ETL

↓ COLOURS

BK WH CUSTOM

↓ SOURCES

- Luminous flux according to Bining: 300lumens
- Colour temperature : de 2400K to 5000K
- Service Range: 70 % of nominal flux after 50 000 hours
- Colour Rendering Index: CRI 90

↓ OPTICAL

- PMMA acrylic lens, efficiency ~90%
- Degrees : 10°, 18°, 28°, 40° and Elliptic

↓ ELECTRICAL (on peg)

- Power supply 700mA
- Reversible polarity and hot plug
- Power consumption to 3W max, excluding supply
- Electrical Classification : Class III SELV device

↓ ELECTRICAL (on tracks or RCA)

- Power supply 24V
- Electric transmission by magnetic contact
- Reversible polarity and hot plug
- Power consumption to 3.5W max, excluding supply
- Electrical Classification : Class III SELV device

↓ MECHANICAL

- Electronic circuit encased in a fire-proof polycarbonate housin
- Fixing by magnetic contact (on track)
- Operating temperature : -5° +40°
- Articulating base
- ROHS components
- Interior use only

↓ SPECIFICITIES

- 3 years guarantee

↓ SPOT NOMENCLATURE

Product Ref.	SD001		
Product specification	Simple peg	A	
	RCA	ARCA	
	Piccolo track	P	
	Slim track magnet	SMA	
Colour	Black	BK	
	White	WH	
	Custom	CU	
Temperature	2400K		24
	2700K		27
	3000K		30
	3500K		35
	4000K		40
	5000K		50
Degrees	10°		10
	18°		18
	28°		28
	40°		40
	Elliptic		ELL
REFERENCE	SD001	A	BK 24 10

↓ MOUNTING NOMENCLATURE

Mounting spec.	Mounting recessed Ø43	ACSFIPATER43	ENCC
	Mounting recessed Ø60	ACSFIPATER60	ENCAC
	Mounting ceiling Ø50	ACSFIPATER50	APPC
	Mounting ceiling X1spot	ACSFIPA1704030	AP1C
	Mounting ceiling X2spot	ACSFIPA1704030	AP2C
Colour	Black		BK
	White		WH
	Custom		CU
REFERENCE		ACSFIPATER43	BK ENCC

↓ RCA TRIM NOMENCLATURE

Product reference		ACSDRCA	APPC
Colour	Black		BK
	White		WH
	Custom		CU
REFERENCE		ACSDRCA	BK APPC

↓ NOMENCLATURES PATERE RCA TRIMLESS

Référence produit	ACSDRCAENCC
-------------------	-------------


Spot D

MOUNTING CONFIG.

REF : SD001



↓ MOUNTING CONFIGURATION




SD001A
Simple peg Ø24.5mm



SD001SMA
Slim track Width 13mm







SD001P
Piccolo track Width 27mm



SD001ARCA
RCA

↓ Beam angle




Spot D

ORDER REFERENCE

REF : SD001




ORDER REFERENCE (MOUNTING NOMENCLATURE)




SD001-A-BK-24
Spot D - Simple peg - Black(BK) - 2400K(24).

+




ACS FIPATER 43 XX ENCC
Fixing mounting recessed
Ø43mm H34mm

or




ACS FIPATER 60 XX ENCC
Fixing mounting recessed
Ø60mm H34mm

or



ACS FIPATER 50 XX APPC
Fixing mounting ceiling
Ø50mm H30mm

or



ACS FIPA 1704030 XX AP1C
Fixing mounting ceiling
(driver in)
x1 spot : 170x40x30mm

or



ACS FIPA 1704030 WH AP2C
Fixing mounting ceiling
(driver in)
x2 spots : 170x40x30mm

ORDER REFERENCE (RCA TRIM NOMENCLATURE)



SD001-ARCA-BK-24
Spot D - RCA - Black(BK) - 2400K(24).

+



ACS DRCA BK APPC
Mounting RCA trim - Black(BK)
(Ø50mm)

=




ORDER REFERENCE (RCA TRIMLESS NOMENCLATURE)




SD001-ARCA-BK-24
Spot D - RCA - Black(BK) - 2400K(24).

+



ACS DRCA ENCC
Mounting RCA trimless

=




Spot D

ACCESSORIES

REF : SD001


SPOT EN

↓ RCA ACCESSORIES




ACSDRCABOUCHONXXC
Finishing cap for RCA trim &
trimless mounting

↓ POWER SUPPLY CONNECTORS




ACSD001COCIRCPXX500
Piccolo circuit with sheath
heat-shrinkable

↓ OPTICAL ACCESSORIES



ACSC001OPNIDABBKD28C
Honeycomb Ø28mm



ACSD001SNOOTBKL10C
Spot D Snoot +10mm